

NCFR-154 is a water soluble saturant for wood, paper and fabric. It may be used with cellulose and cellulose/synthetic blends with minimal effect on fabric hand. It has good temperature stability which yields economical drying speeds and its compatibility makes possible a wide dyestuff selection.

#### APPLICATION:

NCFR-154 may be applied by brushing, dipping, padding or spraying. Drying may be carried out at normal drying temperatures but drying conditions should always be checked experimentally. This product is colorless and odorless when dry.

#### LEVEL OF USE:

The wood, paper or fabric should be clean and absorbent since the presence of dirt, sizing, natural waxes or applied finishes will prevent efficient absorption of NCFR-154. The add-on required depends on the nature of the substrate and the test method required. A coverage of 300 sq. ft./gal. is suggested for wood application. 500-600 sq. ft./gal. coverage is suggested for textile application. It is advisable to determine the add-on required to give satisfactory flammability by a small scale laboratory test before beginning treatment on a large scale.

All statements, recommendations, information contained herein or additional information given orally or in writing pertaining to this product are believed to be accurate and reliable. However, since the manufacturer has no control over the use and application of this product, the manufacturer cannot assume responsibility of any kind, expressed, inferred or implied. The user should not assume all safety measures are indicated or that other safety measures may not be required. All of the risks of use are assumed by the user. Nothing herein shall be construed as a recommendation for use which infringe valid patents or as extending a license under valid patents.

# AMERICAN FIRE COATINGS, INC.

We Give You Time.....  
Manufacturer of

## FLAME ZERO PRODUCTS

Time Saves Lives

NCFR - 154  
CLASS A SATURANT  
WATER-BASED

WOOD, PAPER AND  
FABRIC SATURANT



Registration # C-20401

**IMPORTANT:** Protect this product from freezing. Do not apply if temperature is below 30°F (10°C). Shelf life of unopened containers is six months.

**CAUTION:** NCFR-154 treatment must be renewed after laundering the fabric. NCFR-154 will withstand commercial dry cleaning but aqueous additives or the use of "charged" dry cleaning systems must be avoided.

KEEP OUT OF REACH OF CHILDREN.

Our technical data is based on information we believe to be reliable. It is offered in good faith but without warranty, express or implied, as conditions and methods of use of this product are beyond our control. Purchasers must make their own tests to determine the solubility of this product for their particular end use. Suggestions for use of this product should not be understood as a recommendation for its use with all fabrics.

MANUFACTURED BY:

AMERICAN FIRE COATINGS, INC.  
806 E. MAIN STREET, SUITE J  
BROUSSARD, LA 70518

BATCH # \_\_\_\_\_